

TECHNICAL CHARACTERISTICS

URANIA 100K

PRODUCT CODE: 1339

APPLICATION

Synthetic based lubricant for turbocharged and aspirated diesel engines of commercial vehicles. It permits long drain intervals up to the highest mileages recommended by OEM's on the new generation engines.

SPECIFICATIONS

SAE 10W-40, ACEA E4/E7, API CH-4, IVECO 18-1804, MB 228.5, VOLVO VDS-2, MACK EO-M Plus, MAN 3277, RENAULT RVI RXD PERFORMANCE, CUMMINS CES 20076/20077, MTU OIL TYPE 3

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
SPECIFIC GRAVITY @ 15°C	ASTM D 1298	--	0,870
VISCOSITY @ 100°C	ASTM D 445	cSt	14,5
VISCOSITY INDEX	ASTM D 2270	--	141
FLASH POINT Cl. O. C.	ASTM D 92	°C	> 220
T.B.N.	ASTM D 2896	mg KOH/g	12
POUR POINT	ASTM D 97	°C	- 36
FOAM @ 24°C	ASTM D 892	cc/s	TRACES/0

All technical data is provided for reference only.