

TECHNICAL CHARACTERISTICS

URANIA LD7

PRODUCT CODE: 1353

APPLICATION

Multigrade diesel engine oil for trucks with turbo diesel and naturally aspirated engines. Specifically developed in collaboration with IVECO for new engines. It complies with the requirements of Euro Emission Standards.

SPECIFICATIONS

SAE 15W-40, ACEA E5/E7, API CI-4, IVECO 18-1804 CLASSE T2 E7, MB 228.3, VOLVO VDS-3, MACK EO-N, MTU OIL TYPE 2, CATERPILLAR ECF-1, RENAULT RVI RLD Performance

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
SPECIFIC GRAVITY @ 15°C	ASTM D 1298	--	0,885
VISCOSITY @ 100°C	ASTM D 445	cSt	14,3
VISCOSITY INDEX	ASTM D 2270	--	135
FLASH POINT Cl. O. C.	ASTM D 92	°C	> 210
T.B.N.	ASTM D 2896	mg KOH/g	11,2
POUR POINT	ASTM D 97	°C	< - 27
FOAM @ 24°C	ASTM D 892	cc/s	TRACES/0

All technical data is provided for reference only.