

TECHNICAL CHARACTERISTICS

URANIA OPTIMO 10W-40

PRODUCT CODE: 1359

APPLICATION

Top quality semi-synthetic lubricant for Diesel engines of very high performance commercial vehicles. Formulated to comply with the main international specifications and those of major manufacturers, it offer the highest degree of protection of the engine in even the hardest operating conditions.

SPECIFICATIONS

SAE 10W-40, ACEA E4/E7, API CI-4, MACK EO-M Plus, MAN M3277, MB-Approval 228.5, MTU OIL TYPE 3, SCANIA LDF-2, RENAULT RVI RXD,RLD-2 Performance, VOLVO VDS-3

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	CLEAR
DENSITY 15°C	ASTM D 4052	g/cm ³	0,871
VISCOSITY @ 100°C	ASTM D 445	cSt	14,8
VISCOSITY INDEX	ASTM D 2270	--	158
T.B.N.	ASTM D 2896	mg KOH/g	12,5
FLASH POINT Cl. O. C.	ASTM D 92	°C	> 200
POUR POINT	ASTM D 97	°C	<- 33
FOAM @ 24°C	ASTM D 892	cc/s	TRACES/0

All technical data is provided for reference only.