

## **TECHNICAL CHARACTERISTICS**

**AMBRA MULTI G**

**PRODUCT CODE: 2693**

### **APPLICATION**

Multi-purpose transmission oil (U.T.T.O) for use on tractors, agricultural equipment and earth moving machinery. Suitable for use in traditional gearboxes, Power-Shift and Shuttle-Shift gearboxes, rear transmissions with wet brakes, side final drives, wheel final drives, differentials, hydraulic systems, P.T.U., mechanical and hydrostatic drives, and power steering units.

### **SPECIFICATIONS**

SAE 10W-30, API GL 4, ISO VG 32/46, ZF TE-ML 05F, NH 410 B

### **TEST DESCRIPTION**

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
COLOUR	--	--	L 3
SPECIFIC GRAVITY @ 15°C	ASTM D 1298	--	0,885
VISCOSITY @ 100°C	ASTM D 445	cSt	9,8
VISCOSITY INDEX	ASTM D 2270	--	147
VISCOSITY @ -20°C	ASTM D 5293	cPs	3300
FLASH POINT Cl. O. C.	ASTM D 92	°C	210
POUR POINT	ASTM D 97	°C	< -40
FOAM @ 24°C	ASTM D 892	cc/s	0

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

04/2008